



SPECIFICATION REFERENCE	
320	AGGREGATE BASE
500	CONCRETE
502	CONCRETE STRUCTURES
707	JOINT MATERIAL

UNIFORM STANDARD DRAWINGS  
CLARK COUNTY AREA  
CLARK COUNTY, LAS VEGAS, NORTH LAS VEGAS,  
AND HENDERSON ONLY  
30" ROLL CURB  
RESIDENTIAL AREA  
DATE 11-10-04 DWG NO. 217A PAGE NO. 23A

NOTES:  
1. USE OF ROLL CURB MAY BE RESTRICTED BY SURFACE DRAINAGE CONSIDERATIONS.  
2. SIDEWALK CONSTRUCTION CONTIGUOUS TO ROLL CURB SHALL BE 5 INCHES THICK (MIN).  
3. WHERE LENGTHWISE SLOPE IS LESS THAN 1/4% THE FLOW LINE SHALL BE WATER TESTED.  
4. CONSTRUCT 1/2" EXPANSION JOINT AT ALL COLD JOINTS, AT BEGINNING AND END OF CURB RETURN, AND AT 300 FT. MAX. INTERVALS FOR EXTENDED CURB AND 30 FT. MAX. INTERVALS FOR FORMED CURB. WORKED PLATE JOINTS SHALL BE TYPED AT THE REMAINING 15 FT. INTERVALS. SEE STD. DWG. NO. 23A FOR JOINT DETAILS.  
5. ONE INCH BENTON AT CURB FACE IS OPTIONAL.  
6. CURB JOINTS REPAIRS SHALL BE APPROVED FOR USE OF 30" ROLL CURB IN THE CITY OF LAS VEGAS.  
7. IN NORTH LAS VEGAS, ROLL CURBS ARE PROHIBITED IN AREAS WHERE FLOW LINE GRADE IS LESS THAN 0.8% UNLESS OTHERWISE APPROVED BY CITY ENGINEER.  
8. ALL UTILITY BOXES AND COVERS ADJACENT TO ROLL CURB SHALL BE 16-20 BAYED "TRAFFIC BEARING" TYPE.

**DISCLAIMER NOTE**  
THESE PLANS AND SPECIFICATIONS ARE PREPARED BY STANLEY CONSULTANTS INC. FOR THE USE OF THE CLIENT. THE CLIENT IS RESPONSIBLE FOR THE ACCURACY OF THE INFORMATION PROVIDED AND FOR THE RESULTS OF THE CONSTRUCTION. STANLEY CONSULTANTS INC. DOES NOT WARRANT THE ACCURACY OF THE INFORMATION PROVIDED OR THE RESULTS OF THE CONSTRUCTION. THE CLIENT SHALL BE RESPONSIBLE FOR THE ACCURACY OF THE INFORMATION PROVIDED AND FOR THE RESULTS OF THE CONSTRUCTION. STANLEY CONSULTANTS INC. DOES NOT WARRANT THE ACCURACY OF THE INFORMATION PROVIDED OR THE RESULTS OF THE CONSTRUCTION.

**GEOTECHNICAL NOTE**  
THE CLIENT SHALL BE RESPONSIBLE FOR THE ACCURACY OF THE INFORMATION PROVIDED AND FOR THE RESULTS OF THE CONSTRUCTION. STANLEY CONSULTANTS INC. DOES NOT WARRANT THE ACCURACY OF THE INFORMATION PROVIDED OR THE RESULTS OF THE CONSTRUCTION.

**BENCHMARK**  
BENCHMARK # 20 34" W.C.S.D.  
ELEVATION 2060.4222 FT (NAD 83)  
DESCRIPTION: ALUM CRY 2" DIA. SET IN CONC. 60 FT. HORIZONTAL OR VERTICAL INTERSECTION OF STATIONED 20+34.1066  
R.L.S. TOTAL

**BASE OF BEARING**  
NAD 83 20+34.1066  
LATITUDE 36°02'22.70"N (NAD 83)  
LONGITUDE 119°23'22.70"W (NAD 83)  
ELEVATION 2060.4222 FT (NAD 83)  
DESCRIPTION: ALUM CRY 2" DIA. SET IN CONC. 60 FT. HORIZONTAL OR VERTICAL INTERSECTION OF STATIONED 20+34.1066  
R.L.S. TOTAL

**STATION**  
STATION 1/4 COR 3/4 -  
LATITUDE 36°02'22.70"N (NAD 83)  
LONGITUDE 119°23'22.70"W (NAD 83)  
ELEVATION 2060.4222 FT (NAD 83)  
DESCRIPTION: ALUM CRY 2" DIA. SET IN CONC. 60 FT. HORIZONTAL OR VERTICAL INTERSECTION OF STATIONED 20+34.1066  
R.L.S. TOTAL

**STATION**  
STATION 1/4 COR 3/4 -  
LATITUDE 36°02'22.70"N (NAD 83)  
LONGITUDE 119°23'22.70"W (NAD 83)  
ELEVATION 2060.4222 FT (NAD 83)  
DESCRIPTION: ALUM CRY 2" DIA. SET IN CONC. 60 FT. HORIZONTAL OR VERTICAL INTERSECTION OF STATIONED 20+34.1066  
R.L.S. TOTAL

**STATION**  
STATION 1/4 COR 3/4 -  
LATITUDE 36°02'22.70"N (NAD 83)  
LONGITUDE 119°23'22.70"W (NAD 83)  
ELEVATION 2060.4222 FT (NAD 83)  
DESCRIPTION: ALUM CRY 2" DIA. SET IN CONC. 60 FT. HORIZONTAL OR VERTICAL INTERSECTION OF STATIONED 20+34.1066  
R.L.S. TOTAL